



Refrigerant Leak Detector

A2L Certified



Functions

- Detects industry standard refrigerants

Features

- A2L Certified
- Solid electrolyte semiconductor sensor
- Digital numeric leak size indicator
- 3 Sensitivity levels
- Visual LED leak alarm
- Automatic calibration & ambient level reset
- Splash resistant
- Worklight
- 2-Year limited warranty

Applications

Ensuring system is installed and setup properly
Verifying that system connection seals are still working and not wearing down
Finding leaks is the first step in preventing costly damage
Confirm that local and state level laws and guidelines are being met





Includes

- Sensors filters 5 (RLDTF)
- Leak test vial (RLDLS)
- Batteries 4 (AA)
- Hard carrying case
- Manual

Specifications

Sensitivity	.05 oz/yr R134a .025 oz/yr R22
Sensor Life	> 300 Hours
Response Time	≤1sec
Power Supply	4 (AA) Alkaline
Battery Life	4 - 6 Hrs. Continuous
Warm-Up Time	<20 Seconds
Probe Length	17 inches
Numerical Display	7 Segment Digital (1-9)
Display Refresh Rate	3/sec.
Operating Temperature	-24 to 125°F (-31 to 52°C)
Operating Humidity	<95% non-condensing
Operating Altitude	<10,000 ft.
Storage Temperature	-4 to 122°F (20 to 50°C)
Pollution Degree	4
Weight, lbs	1.5 Lbs
Certifications	SAE J2791, SAE J2913 (A2L Certified) EN14624-2012 ASHRAE 173-2012
Warranty	2-Year limited warranty

Refrigerant List

Common refrigerants, but not limited to

R11	R407A	R434A (RS-45)
R12	R407C	R438 (MO99)
R13	R407F	RA438A (MU99)
R22	R408A	R448A
R23	R409A	R449A
R32	R410A	R453A
R113	R414B (Hotshot)	R458A
R114	R416A	R500
R123	R417A	R502
R1234YF	R417C (Hotshot 2)	R503
R124	R420A	R507A
R125	R421A	R508B (Suva95)
R134A	R421B	R513A
R401A (MP39)	R422A	R600A (Isobutane)
R401B	R422B(NU22B)	R601 (Pentane)
R402A	R422C (One shot)	R601A (Isobutane)
R402B	R422D	R1233ZD
R404A	R424A	R12342E
R406A	R427A	

Downloads



Manual



Data Sheet

H26-901



Made in USA