



INDUSTRIES LIMITED

Specification:

AXIOM Industries Hydronic System Feeder: SF100-HP-L

Hydronic system feeder shall be AXIOM INDUSTRIES LTD. Model SF100-HP-L. System shall include 383 litre (100 US gallon) storage/mixing tank with cover; pump suction hose with inlet strainer; pressure pump with thermal cut-out; integral pressure switch; integral check valve; cord and plug; pre-charged accumulator tank with EPDM diaphragm; manual diverter valve for purging air and agitating contents of storage tank; pressure regulating valve adjustable (173 – 600 KPa; 25 – 85 psig) complete with pressure gauge; built-in check valve; union connection; 12 mm (1/2”) x 900 mm (36”) long flexible connection hose with check valve; low level pump cut-out. Pressure pump shall be capable of running dry without damage. Power supply 115/60/1 0.9 A. Unit shall be completely pre-assembled and certified by a recognized testing agency to CSA standard C22.2 No 68.

OPTION

2PRV – Second Pressure Reducing Valve, Pressure Gauge, System Connector Hose and Check Valve to allow for independent pressure supply to a second system.

RIA10-1-SAA – Low Level Alarm Panel c/w Remote Monitoring Dry Contacts and Selectable Audible Alarm.
See RIA10-1-SAA product page for Alarm Panel Specifications



Certified to CAN/CSA
C22.2 No. 68

9901055
Conforms to UL73

